
Backward curved centrifugal fans

KABB/KABT Series

Serial KABT

KABB/4-4000/355 0,55KW DES 230V50HZ VE



Cabinet fans manufactured from galvanised steel sheet with double thickness side panels lined with 17 mm thickness of fireproof fibreglass acoustic insulation (M0). Circular duct connection flange on the inlet.
KABB / KABT incorporates direct driven aluminium backward curved centrifugal impeller with motor fitted outside of the air stream.
Supplied with galvanized drip tray and copper drain.



Motors
- KABB: Single-phase 4 pole motor 230V-50Hz, IP55, class F, with thermal protection, speed controllable by tension.
Maximum temperature around the motor:
KABB/4-3000/315: 70ºC
KABB/4-4000/355: 50ºC
KABB/4-6000/450: 40ºC

- From KABT/4-3000/315 to KABT/4-9000/500:
Three-phase 4 pole motor 230/400V-50Hz, IP55, Class F, with thermal protection, speed controllable by inverter.

- KABT/4-12000/560:
Three-phase 4 pole motor 400V-50Hz, IP55, Class F, with thermal protection, speed controllable by inverter.

Additional information
Working temperature from -20ºC to 100ºC.

Technical data

© S&P Sistemas de Ventilación SLU