



DEHUMIDIFIERS DHUM-EN Series

Serial DHUM-E

DHUM-20 E

Domestic dehumidifiers that are compact, portable and easy to move and setup.
Available in 4 versions according to the dehumidification capacity: 12l., 16l., 20l. and 30l.

Features:

- Super-silent rotary compressor.
- Electronic humidistat, allowing you to select the required level of humidity, and ambient humidity indicator.
- 2 speeds and 3 operating modes: MANUAL, CONTINUOUS & AUTOMATIC. Automatic mode will select the level of humidity based on the ambient temperature.
- Programmable 1-24 hour run-on timer.
- Anti-frost function: activates when the ambient temperature falls below approximately 15°C.- Automatic reset in the event of a power cut.
- Warning sign when the water tank saturates.
- Automatic shut-off function: activates when the water tank is full.
- Carrying handles.
- DHUM-EN: Operating temperature 5-32°C.

DHUM-EN: According to European Regulation number 517/2014, concerning to the greenhouse gases.



Technical data

Technical characteristics

Model	Voltage 50Hz (V)	Power (W)	Absorbed current (A)	Sound power level (dB(A))	Dehumidification capacity (litres/24h.) (30°C/80 R.H.)	Water tank capacity (L)	Surface area of influence* (m²)	Operating temperature	Electronic humidistat	Speeds	Coolant	Colour	Weight (kg)	Dimensions (mm)
DHUM-12 E	230	260	1,2	40	12	2	30	5 - 32°C	•	2	R134A	White RAL 9003 / Black RAL 9005	11,2	365x220x490
DHUM-16 E	230	410	1,8	42	16	2	40	5 - 32°C	•	2	R134A	White RAL 9003 / Black RAL 9005	13,2	365x220x490
DHUM-20 E	230	480	2,1	42	20	2	45	5 - 32°C	•	2	R134A	White RAL 9003 / Black RAL 9005	13,7	365x220x490
DHUM-30 E	230	650	3	46	30	7	50	5 - 32°C	•	2	R410A	White RAL 9003 / Black RAL 9005	18,5	481x286x628

* Information provided as guidance for ceiling heights of 2.5 m.