



## Wall fans

### ARTIC PM/ PRC GR Series

## Serial ARTIC-405 PM/PRC

### ARTIC-405 PM GR

Wall fans with 3 speed controller, timer and detachable proof guard.

#### Characteristics

- The ARTIC-405 PM GR model is equipped with two pullcords that facilitate speed control and fan swing.
- The ARTIC-405 PRC GR model includes remote control and BREEZE and NIGHT functions.

#### Breeze Function

The fan alternates different speeds simulating a natural breeze.

#### Night Function

The fan alternates between the various Breeze functions.



## Technical data

### Technical characteristics

Model	Voltage 50Hz (V)	Nominal power (W)	Intensity (A)	Maximum airflow* (m³/h)	Maximum air output speed (m/s)	Maximum sound power level (dB(A))	Adjustable timer	Nº speeds	Remote distance (with support wall)	Fan position		Motor with thermal protection	Cable length (mm)	Colour	Weight (kg)	Dimensions (mm)		Wiring diagram** (nº)
										Inclinable	Fixed / oscillating					Ø Propeller	Height	
ARTIC-405 PM GR	230	50	0,22	3.300	2,65	62	10 to 180 min.	3		•	•	•	1.500	Grey	5	400	560	37
ARTIC-405 PRC GR	230	50	0,22	3.300	2,65	62	1 a 8h	3	•	•	•	•	1.500	Grey	5	400	560	37

\* The indicated airflow include induced airflow.

\*\* See section of Wiring Diagrams.

\*\*according to IEC 60879 regulation.

## Function

When the NIGHT function is selected	The fan goes through the following cycle:	
Slow Speed	BREEZE	Slow Speed (Permanent)
Medium Speed	BREEZE	Medium Speed (30 min.) Slow Speed (Permanent)
High Speed	BREEZE	High Speed (30 min.) Medium Speed (30 min.) Slow Speed (Permanent)