Fixed Hoods for Professional Kitchens

MAXFIL2 COMPACT PRO Series

Serial MAXFIL2 COMPACT PRO SERIES



MAXFIL2 COMPACT PRO 500 LG 3000

Capture, extraction and filtration of pollutants and heat in commercial or collective kitchens.
Single backed or double central.
Single modules of length 1000, 1500, 2000, 2500 and 3000 mm.
Without visor or with depth of 1000, 1250, 1500 or 1750 mm.
Height of 400 mm and 500 mm.
Constant hood height for a maximum capture volume.
Self-supporting construction without visible attachment or sharp edges for cleaning without risk of injury.
Side reinforcement, 15/10mm galvanized steel, height 50mm, integrated into the hood, ensuring the rigidity of the assembly.
Setting the level from inside the hood and clip-in fastener caps.
Braced at sensor end for rigid join between two modules, while allowing a large air passage.

Visible faces austenitic stainless steel AISI 304 (1.4301) with a brushed finish SB.
- Central hoods assembled back to back using two hoods backed with partitions.
- Sides without obvious elements such as rivets and studs.
- Rear and upper surfaces in galvanized steel.
- Standard filter galvanized material, stainless steel frame M0397x472x25 mm.
- Stainless steel closure plate.
- Peripheral gutter.
- Drain with stainless steel - threaded plug Gas 1/2.

Packaging: Packaged on pallet in heat-shrink film.

On request
- Rear assembly plate without visible screws and top panel in stainless steel.
- Longer and special lengths available.
- Accessories (ring plate, balancing guillotine damper, waterproof light etc.).
-Motorised hoods, laundries, ovens, comfort, comfort 90/10, 30 to 60% induction, closed filter ceilings, modular ceilings etc.


Technical data

Technical characteristics


Model	Length (mm)	Weight (Kg)				
		Without Extended	Hood 1000	Hood 1250	Hood 1500	Hood 1750
MAXFIL₂ COMPACT PRO 500 LG 1000	1000	32	45	50	54	60
MAXFIL₂ COMPACT PRO 500 LG 1500	1500	41	58	64	69	76
MAXFIL₂ COMPACT PRO 500 LG 2000	2000	55	76	83	89	97
MAXFIL₂ COMPACT PRO 500 LG 2500	2500	64	89	98	105	114
MAXFIL₂ COMPACT PRO 500 LG 3000	3000	74	103	114	121	131

Dimensions

Optional lights - Supplied undrilled




Underlined = size of 400 model
Normal = size of 500 model



Unit	Total length*	Length of collection	Nº of vents for extraction	Nº of filters / sheets	A	B	D	E	Extended 1000		Extended 1250		Extended 1500	
									F	G	F	G	F	F
1000	1004	1000	1	2 / 0	502	-	968	920	185	695	310	695	810	695
1500	1504	1500	1	2 / 1	752	-	1468	1420	185	1325	310	1325	810	1325
2000	2004	2000	2	2 / 2	514	976	1968	1920	185	1325	310	1325	810	1325
2500	2504	2500	2	3 / 2	645,5	1213	2468	2420	185	1325	310	1325	810	1325
3000	3004	3000	2	3 / 3	645,5	1713	2968	2920	185	1325	310	1325	810	1325

* Total length of assembled modules: 3504, 4004, 4504, 5004, 5504, 6004

Installation



© S&P Sistemas de Ventilación SLU