



Axial Smoke Extractor Jet Fans TJHT-TJHU Series

Serial TJHT-TJHU

TJHU/2/4-400-C

Axial jet fans to induce air movement in enclosed car parking, tunnels and large spaces. Suitable for ventilation and one off emergency smoke operation at F400 or F300.

TJHT series: reversible.

TJHU series: unidirection.

Description

Diameters from:

TJHT series: 315 to 630mm, fully reversible.

TJHU series: 315 to 400mm, unidirection.

Impeller is cast aluminum alloy in accordance with EN 1706, and balanced in accordance with ISO 14694: G 6.3.

Fan duct and 2 mounting feet are steel in accordance with EN 10130-99, and hot dip galvanized in accordance with EN 1461: 1999.

Fan external electrical terminal box.

Two circular sound attenuators in galvanized sheet steel, with flared inlet and acoustic media.

Supplied with inlet and outlet steel guard.

Impeller with 6 (TJHT) or 7 (TJHU) blades.

Fan approved in accordance EN12101-3.

For transportation, size up to 400 is supplied complete. Diameter from 450 to 630 can be supplied in 3 pieces.



Motors

TJHT series: IEC, from 80 to 160, 3 phase 380-415V-50Hz, IP55, Class H, F400-120 and F300-120.

TJHU series: IEC, from 80 to 90, 3 phase 380-415V-50Hz, IP55, Class H, F400-120 and F300-120. Class F at F200-120.

Available in 60Hz.

Two speed 2/4 pole Dalhander winding.

Ambient temperature: -20°C to +40°C.

Working temperature from -20°C to +40°C.

On request

Single speed 2 pole motor.

Inlet guard and steel discharge deflector for unidirectional airflow.

Inlet and outlet steel discharge deflector for reversible airflow.

Factory fitted IP65 isolator in place of electrical terminal box. Isolator also available as an accessory for use with standard terminal box fan.

External painting to RAL colour.

Technical data

Acoustic characteristics

Sound power levels LwA ref. 1pW tested in accordance with ISO 13347:2004.

TJHT (2 pole)

Form A	63	125	250	500	1000	2000	4000	8000	LwA
315	58	67	77	78	71	68	64	56	81
355	61	70	81	80	75	73	70	47	85
400	64	73	85	82	80	78	75	67	88
450	68	76	89	84	84	83	80	73	92
500	71	79	93	86	88	87	84	78	96
560	74	82	97	89	92	92	89	83	100
630	77	85	101	91	96	97	94	88	104

Form B	63	125	250	500	1000	2000	4000	8000	LwA
315	56	65	77	78	70	68	65	57	81
355	60	68	79	80	74	73	69	48	84
400	64	72	82	81	78	77	73	67	87
450	68	75	85	83	81	82	78	72	89
500	71	78	87	84	85	86	82	76	92
560	75	81	90	85	88	90	86	81	96
630	79	84	92	87	92	94	90	86	99

TJHT (4 pole)

Form A	63	125	250	500	1000	2000	4000	8000	LwA
315	43	52	62	63	56	53	49	41	66
355	46	55	66	65	60	58	54	32	70
400	49	58	70	67	65	63	60	52	73
450	53	61	74	69	69	68	65	58	77
500	56	64	78	71	73	72	69	63	81
560	59	67	82	73	77	77	74	68	85
630	62	70	86	76	81	82	79	73	89

Form B	63	125	250	500	1000	2000	4000	8000	LwA
315	41	50	62	63	55	53	49	42	66
355	45	53	64	65	59	58	54	33	69
400	49	57	67	66	63	62	58	52	72
450	53	60	70	68	66	67	63	57	74
500	56	63	72	69	70	71	67	61	77
560	60	66	75	70	73	75	71	66	81
630	63	69	77	71	77	79	75	71	84

TJHU (2 pole)

Form B	63	125	250	500	1000	2000	4000	8000	LwA
315	61	63	71	72	75	72	66	61	79
355	64	66	75	75	78	76	70	64	83
400	67	71	76	77	82	81	76	70	86

TJHU (4 pole)

Form B	63	125	250	500	1000	2000	4000	8000	LwA
315	40	56	54	58	56	50	45	38	63
355	44	59	58	60	61	54	49	42	66
400	46	63	62	69	62	60	55	46	72

Technical characteristics

Model	Speed (rpm)	Thrust (N)	Airflow (m³/h)	Air velocity (m/s)	Motor power* (kW)	Maximum absorbed current (A)	Sound pressure level** (LpA)		Weight (kg)
							Form A***	Form B***	
TJHT REVERSIBLE - 1 speed 2 POLE									
TJHT/2-315-CN	2790	24	4.500	16	0,75	1,6	64	64	57
TJHT/2-355-CN	2810	40	6.500	18	1,1	2,3	67	66	76
TJHT/2-400-CN	2870	60	9.000	20	1,5	4,2	71	69	89
TJHT/2-450-C	2840	85	12.100	21	2,2	4,5	75	72	133
TJHT/2-500-C	2890	144	17.500	25	4	7,5	78	75	165
TJHT/2-560-C	2925	235	25.000	28	7,5	13,6	82	78	220
TJHT/2-630-C	2945	387	36.100	33	15	27	87	82	290
TJHT REVERSIBLE - 2 speed 2/4 POLE									
TJHT/2/4-315-CN	2820/1400	24	4.500	16	0,8/0,2	1,9/0,6	64/49	64/49	57
TJHT/2/4-355-CN	2810/1390	40	6.500	18	1,1/0,25	2,4/0,75	67/52	66/51	76
TJHT/2/4-400-CN	2900/1435	60	9.000	20	1,5/0,37	4,2/1,3	71/56	69/54	89
TJHT/2/4-450-C	2845/1420	85	12.100	21	2,2/0,5	4,6/1,5	75/60	72/57	134
TJHT/2/4-500-C	2890/1440	144	17.500	25	4,4/1,1	8,6/2,8	78/63	75/60	166
TJHT/2/4-560-C	2930/1470	235	25.000	28	8/2	15,3/4,8	82/67	78/63	223
TJHT/2/4-630-C	2950/1470	387	36.100	33	16/4	30,5/9,6	87/72	82/67	311
TJHU UNIDIRECTIONAL - 1 speed 2 POLE									
TJHU/2-315-BC	2790	25	4.600	16	0,75	1,6	-	62	56
TJHU/2-355-BC	2810	43	6.800	19	1,1	2,3	-	66	75
TJHU/2-400-BC	2870	68	9.700	21	1,5	3	-	70	88
TJHU UNIDIRECTIONAL - 2 speed 2/4 POLE									
TJHU/2/4-315-BC	2820/1400	25	4.600	16	0,8/0,2	1,9/0,6	-	62/46	56
TJHU/2/4-355-BC	2810/1390	43	6.800	19	1,1/0,25	2,4/0,75	-	66/49	75
TJHU/2/4-400-BC	2900/1435	68	9.700	21	1,5/0,37	3,5/1,3	-	70/55	88

* May depend on motor used.

** Sound pressure at 3m, hemispherical propagation, in free field conditions, for comparison.

*** TJHT series: Form A air over motor > impeller, Form B air through impeller > motor. TJHU series: Form B only.

Reference

T	J	H	T	/	2/4	-	6	3	0	C/I	16/4	F400	400 V	50 Hz
1					2		3			4	5	6	7	8

- 1 - Series: TJHT reversible, TJHU unidirection, for emergency smoke operation and ventilation.
- 2 - Motor speed (poles).
- 3 - Nominal diameter.
- 4 - C = Terminal box (standard). I = Isolator (optional).
- 5 - Emergency operation designation.
- 6 - Temperature class.
- 7 - Nominal electrical supply.
- 8 - Frequency (Hz).