

## Whole House Extract Units Auto-Adjustable Ventilation Groups VENTURIA-E 2018 Series

### VENTURIA-E 3V

Auto-adjustable whole house extract group that ensures permanent renovation of air in single-dwellings. Conceived to run continuously, it guarantees the requirements established in the Technical Building Code. Equipped with centrifugal fan and 1-speed 230V-50Hz motor. The system should include airflow regulators or suitable auto-adjustable valves in the wet areas of the house (bathrooms and kitchen) and ECA air vents in the dry areas (living room, bedrooms), via which outside air will be introduced.

#### Characteristics

- 3 inlet valves of Ø80 mm for toilets and bathrooms, removable by means of a quarter turn and fitted with two ring clamps allowing a quick and watertight installation of the ducts without tools and clamps. The fourth inlet valve will be covered.
- Exhaust automatically regulated valves for kitchen of Ø125 mm.
- Discharge port of Ø125/160 mm allowing to expel the exhaust air to the outside.
- Terminal box fitted.
- Four plastic covers to block the exhaust valves that are not operating.
- Sleeve equipped with hooks that make easier the fastening of the extract duct.



#### Attributes



#### Easy maintenance

3 opening and closing flanges allowing the dismantling of the assembly motor-extractor without the need of disconnecting the ducts and the exhaust valves.





#### **Inlet valves for toilets and bathrooms**

Removable by means of a quarter turn and fitted with two ring clamps allowing the fixing of the supply duct.



#### **Inlet valves for toilets and bathrooms**

Removable by means of a quarter turn and fitted with two ring clamps allowing the fixing of the supply duct.



#### **Continuous fresh air**

The Venturia-E 2018 extract system is conceived to run continuously, ensuring the permanent air renewal in residential houses.