



VMC Viviendas unifamiliares- Grupos de ventilación autorregulables

Serie VENTURIA-E 2018

VENTURIA-E 3V

Auto-adjustable whole house extract group that ensures permanent renovation of air in single-dwellings. Conceived to run continuously, it guarantees the requirements established in the Technical Building Code. Equipped with centrifugal fan and 1-speed 230V-50Hz motor. The system should include airflow regulators or suitable auto-adjustable valves in the wet areas of the house (bathrooms and kitchen) and ECA air vents in the dry areas (living room, bedrooms), via which outside air will be introduced.

Characteristics

- 3 inlet valves of Ø80 mm for toilets and bathrooms, removable by means of a quarter turn and fitted with two ring clamps allowing a quick and watertight installation of the ducts without tools and clamps. The fourth inlet valve will be covered.
- Exhaust automatically regulated valves for kitchen of Ø125 mm.
- Discharge port of Ø125/160 mm allowing to expel the exhaust air to the outside.
- Terminal box fitted.
- Four plastic covers to block the exhaust valves that are not operating.
- Sleeve equipped with hooks that make easier the fastening of the extract duct.



Caractéristiques



Maintenance facile

3 clips permettant le démontage complet sans déconnecter les conduits et les bouches.



Montage

Cordelette de suspension anti-vibratile pour montage en combles ou faux-plafond.
Evite aux vibrations du caisson de se diffuser dans le bâti.



Renouvellement de l'air permanent

Le système d'extraction Venturia assure le renouvellement permanent des maisons individuelles au travers de bouches d'extraction dans les pièces humides (cuisines, salles-de-bainset WC) et les entrées d'air dans les pièces principales (chambres et salon).